



H2 (High Speed) Direct Drive Aluminum Elevator

Industrial Duty Integrated with a New Ultra Modern Appeal

- All Aluminum and Stainless Steel Construction
- Low Draft Design
- Very Modern Compact Drive Units
- Stainless Steel Equalizer Arms with Quad Upper Rollers
- Aluminum Bunks (Standard up to 20,000 lbs. if applicable)
- Stainless Steel Cables
- Adjustable Heavy Duty Guide Poles
- Piling or Seawall Mount
- Standard Angle is 25° (Available in Various Angles including Vertical)
- 15 Year Limited Warranty

Options:

- SEArmor Corrosion Resistant Winders for Long Lasting Durability
- Wash Down Stainless “Hurricane” Motors
- Wireless Remote Control
- Auto Stop and Limit Switch
- Complete Disconnect Switch
- Stainless Steel Wash Down “Hurricane” Motors
- Underwater Bracing (for Deepwater Applications)
- Aluminum Bunks (Standard up to 20,000 lbs. if applicable)
- Cable Retention System



Specifications

***See our “Complete list of Other Accessories”

Size	Horse Power	Volt and Amperage	Cable Size and Length	Vertical Travel	Track Size	Max. Beam	Cradle Dimensions	Bunks	Pile Size
6,000 lb.	(2) 1 1/2 HP	240V/25A	5/16” x 30’ Stainless Steel	12’	6” x 4” x 25’ I-Beam	8’ 0”	7’ Dual Forks	3” x 8” x 12’ Carpeted Bunks	8”
10,000 lb.	(2) 1 1/2 HP	240V/25A	5/16” x 30’ Stainless Steel	12’	8” x 5” x 25’ I-Beam	9’ 0”	8’ Dual Forks	3” x 10” x 12’ Carpeted Bunks	10”
14,000 lb.	(2) 2 HP	240V/30A	5/16” x 45’ Stainless Steel	12’	10” x 6” x 25’ I-Beam	10’ 0”	8’ Dual Forks	3” x 10” x 12’ Carpeted Bunks	10”
20,000 lb.	(2) 2 HP	240V/30A	3/8” x 56’ Stainless Steel	11’	12” x 7” x 25’ I-Beam	12’ 0”	10’ Dual Forks	3” x 10” x 14’ Carpeted Bunks	12”
27,000 lb.	(2) 2 HP	240V/30A	7/16” x 60’ Stainless Steel	11’	10” x 6” Double Tracks	12’ 0”	10’ Quad Forks	3” x 12” x 18’ Carpeted Bunks	CALL FOR SPECS.

* Specifications are subject to change without notice *